



TT BOILERS ELECTRIC STEAM BOILER			Type DH2											
			195	234	273	312	351	390	429	468	507	585	720	1000
Nominal Output (= Consumed Power)	kW		195	234	273	312	351	390	429	468	507	585	720	1000
Current at 3 x 400 V	A		281	338	394	450	507	562	619	675	732	844	1040	1450
Steam Capacity at 6 bar and Feed Water Temperature 20°C	kg/h		255	305	355	405	455	510	560	610	660	785	965	1350
Steam Capacity at 6 bar and Feed Water Temperature 90°C	kg/h		285	340	400	455	515	570	630	685	740	885	1090	1500
Total Volume	L		400				560				745	910	1250	
Weight - Empty	kg		500				670				730	1300	1800	
Weight - Service	kg		900				1230				1475	2200	3100	
Diameter	D	mm	800				900				1000	1000	1200	
Width	W	mm	1160				1260				1360	1600	1800	
Length	L	mm	2050				2100				2150	3200	3600	
Height	H	mm	1250				1350				1450	1750	2000	
Connection - Low Pressure Steam Design Pressure 1 bar gauge	DN	mm	50		65		80				100	125		
		-	2"		2 1/2"		3"				4"	5"		
Connection - High Pressure Steam Design Pressure 6 bar gauge	DN	mm	25	32	40			50			65	80		
		-	1"	5/4"	1 1/2"			2"			NA	NA		
Connection - High Pressure Steam Design Pressure 10 bar gauge	DN	mm	25		32		40				65	80		
		-	1"		5/4"		1 1/2"				NA	NA		

